



PDG-DSU21B

- Resolution: 800 x 600 (SVGA)
- Brightness: 2300 ANSI Lumens
- Contrast Ratio: 2000:1
- Weight of only 2.75kg
- Built in Speaker
- Vertical Keystone Correction $\pm 15^\circ$
- 5 Segment Colour Wheel
- 3 Year Warranty

PDG-DSU21B

TECHNICAL DETAILS	PDG-DSU21B
Category	Business & Education
Panel	1 x 0.55" DMD Chip (4:3)
Lamp	180W UHP
Brightness ANSI lumens	2300 (Normal Mode), 1840 (Eco Mode)
Lamp Service Life	3,000 h (Eco Mode), 2500 h (Normal Mode)
Fan Noise	32dBA (Eco Mode), 35dBA (Normal Mode)
Standard Lens	F=2.51-2.69, f=21.95-24.18mm
Throw Distance Ratio	1.92-2.12:1
Throw Distance	1.2m – 12m
Contrast Ratio	2000:1
Resolution in pixels	800 x 600
Image size min-max (diagonal)	30 – 300"
Uniformity	80%
Bandwidth/Frequency	25-135MHz, Horizontal 31kHz – 79kHz, Vertical 50Hz – 85Hz
Colour Systems	PAL / NTSC / SECAM / NTSC4.43 / PAL-M / PAL-N
Connections	Input 1: D-sub15 Input 2: RCA x 1 Input 3: S-Video Control: Mini Din6 (RS232), USB-B type (Mouse Control)
Keystone Correction	vertical +/- 15°
Up/Down Ratio	13.3:-1
HDTV Signals	480i, 480p, 576i, 576p, 720p, 1080i
Computer Compatibility	WXGA / SXGA / XGA / SVGA / VGA
Zoom/Focus	Manual focus, Manual zoom (x1.1)
Power Consumption/Voltage	200W (Eco Mode) 230W (Normal Mode) 7.1W (Standby)
Warranty	3 years
Dimensions (W x H x D)	271 x 95 x 223mm
Weight	2.75kg
Standard Accessories	Power Cord, Computer Cable (D-sub15-D-sub15), Remote Control, Instruction Manual
Optional Accessories	POA-CAC-VCL2 (soft Carry Bag), POA-CA-COMPVGA (Component-D-sub15 cable)
Lenses	Standard lens

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007

